



Item no: 0223781

Vacuplus MINI Xi10-2

The Vacuplus ejectors are highly efficient, light weight, robust and easy to use. The portfolio consists of products targeted to customer that need a great and simple vacuum ejector for low to mid-range applications. The products in our Vacuplus portfolio complement our existing ejectors by offer a... straightforward assortment that is developed with the learnings of over 70 years of experience in vacuum automation.

- Small and compact sizes
- Symmetric vacuum interfaces on top and bottom ensures flexible installation
- Patented COAX® technology

General

Item number, alternative	VP04.002X
Material	POM, SS, AL, NBR
Noise level	60 - 74 dBA
Temperature	-10 - 50 °C
Weight, max.	72 g

Performance

Feed pressure, max.	0.7 MPa
---------------------	---------

Feed pressure	Air consumption	Vacuum flow (NI/s) at different vacuum levels (-kPa)										Max vacuum
		0	10	20	30	40	50	60	70	80	-kPa	
MPa	NI/s											
Mini slim Xi10-2 A - 0.5	0.46	0.75	0.63	0.49	0.33	0.19	0.15	0.11	0.07	0.04	94	

Feed pressure	Air consumption	Evacuation time (s/l) to reach different vacuum levels (-kPa)										Max vacuum
		10	20	30	40	50	60	70	80	90	-kPa	
MPa	NI/s											
Mini slim Xi10-2 A - 0.5	0.46	0.14	0.32	0.57	0.97	1.57	2.27	3.47	5.27	8.867	94	

Dimensional drawings 

